



# FLEXX-FIT™



## FLEXIBLE BRAKE LINES

**FAST • CORROSION-PROOF • SHOCK-RESISTANT • ECONOMICAL**



FLEXX-FIT™ lines are not brake hoses. FLEXX-FIT™ lines are 12" flexible brake lines. Use them anywhere a more flexible, shock-resistant, and corrosion-proof section of line is needed. No need to hunt down expensive application-specific OE assemblies.

- 4,000 psi working pressure
- 7,000 psi burst pressure
- -50°F to 250°F (-45°C to 121°C)
- Compatible with all brake fluids
- Meets FMVSS-106 standards
- Zinc Dichromate coated fittings
- Anti-corrosion link technology

PATENT PENDING



### AVAILABLE FOR DOMESTIC & IMPORT

Part No.	Description
FX-312	3/16" x 3/8-24 Inverted
FX-412	1/4" x 7/16-24 Inverted
FX-712	6mm x M12x1.0 Bubble
FXB-312	3/16" x 3/8-24 Bubble
FXE-312	3/16" x M10x1.0 Bubble
FXJ-312	3/16" x M10x1.0 Inverted



O-ring seal built into fittings keeps out corrosion and contamination.

Thread/flare-type marked on fitting.





# FLEXX-FIT™

## FLEXIBLE BRAKE LINES WALL DISPLAYS



### FXD-22 – FLEXX-FIT™ WALL DISPLAY

Part No.	Description	QTY
FX-312	3/16" x 3/8-24 Inverted	5
FX-412	1/4" x 7/16-24 Inverted	5
FX-712	6mm x M12x1.0 Bubble	5
FXB-312	3/16" x 3/8-24 Bubble	5
FXE-312	3/16" x M10x1.0 Bubble	5
FXJ-312	3/16" x M10x1.0 Inverted	5



### FXD-21 – FLEXX-FIT™ WALL DISPLAY (NO LINES)



Scan to watch the FLEXX-FIT™ video.

**USE FLEXX-FIT™ LINES AND POLY-ARMOUR® OR NICOPP® TOGETHER FOR A COMPLETE SOLUTION ON THESE APPLICATIONS AND MORE!**



**ABS Controllers**



**Motorcycles**



**Wheel Cylinders**



**Master Cylinders**



**Trailers**

