



SAFETY DATA SHEET

Issuing Date 13-Nov-2014

Revision Date 15-Nov-2018

Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Thread-Magic Anti-Seize Grease Compound

Other means of identification

Product Code(s) TMPC-1, TMP-1A, TMP-1, TMP-1ASP

Synonyms Anti-Seize Grease

Recommended use of the chemical and restrictions on use

Recommended Use Avoid stuck plugs and bolts, heat resistant, assure easy installation and removal. Use the stick like a crayon. Thread-Magic withstands temps to 1200F (649C). Even works on bi-metal applications where seizing problems can be severe. Assure easy removal on aluminum and cast iron components to prevent seizing, galling, and damage during disassembly. Use on lug nuts, brake lube assembly and anchor pins, engine head bolts, spark plug threads, oxygen sensor threads, exhaust manifold studs, EGR fittings, starter & alternator bolts, and more!

Uses advised against No information available

Supplier's details

Supplier Address
AGS Company
Automotive Solutions LLC
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number CHEM-TEL, INC.
24 Hour Emergency Contact 1-800-255-3924

2. HAZARDS IDENTIFICATION


Classification

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Germ Cell Mutagenicity	Category 1B
------------------------	-------------

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word	Danger	
Hazard Statements	• May cause genetic defects	
		
Appearance	Silver.	Physical State Semi-Solid.
		Odor Petroleum.

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.

General Advice

- If exposed or concerned: Get medical attention/advice

Storage

- Store locked up.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

Toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Anti-Seize Grease

Chemical Name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	60-100	*
Stearic acid	57-11-4	5	*
Silica	7631-86-9	1-5	*
Aluminum	7429-90-5	1-5	*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	1.7	*
Aromatic solvent	64742-95-6	1-5	*
Copper	7440-50-8	0.1-1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of necessary first-aid measures**

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.
Skin Contact	Wash skin with soap and water.
Inhalation	Move to fresh air.
Ingestion	Clean mouth with water and afterwards drink plenty of water.

Most important symptoms/effects, acute and delayed**Most Important Symptoms/Effects** No information available**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available**Specific Hazards Arising from the Chemical**

No information available.

Explosion Data**Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions** Ensure adequate ventilation.**Environmental Precautions****Environmental Precautions** Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information. Collect spillage.**Methods and materials for containment and cleaning up****Methods for Containment** Prevent further leakage or spillage if safe to do so.**Methods for Cleaning Up** Pick up and transfer to properly labeled containers.**7. HANDLING AND STORAGE****Precautions for safe handling****Handling** Handle in accordance with good industrial hygiene and safety practice.**Conditions for safe storage, including any incompatibilities****Storage** Keep containers tightly closed in a dry, cool and well-ventilated place.**Incompatible Products** None known based on information supplied.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stearic acid 57-11-4	TWA: 10 mg/m ³ inhalable particulate matter TWA: 3 mg/m ³ respirable particulate matter	-	-
Silica 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays Action Level: 25 µg/m ³ (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

No special protective equipment required.
No special protective equipment required.
If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Semi-Solid.	Appearance	Silver.
Odor	Petroleum.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	Not applicable	None known
Melting Point/Range	Not determined	None known
Boiling Point/Boiling Range	Not determined	None known
Flash Point	380 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	

Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	1.0501	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	Negligible	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	Not determined	None known

Flammable Properties No data available.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) 1.40%

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	There is no data available for this product.
Eye Contact	There is no data available for this product.
Skin Contact	There is no data available for this product.
Ingestion	Ingestion may cause stomach discomfort.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

heavy naphthenic			
Stearic acid	-	5 g/kg (Rabbit)	-
Dimethyl silicone polymer with silica	> 5000 mg/kg (rat)	> 2000 mg/kg	-
Naphtha (petroleum), hydrotreated heavy	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m ³ (Rat) 4 h
Aromatic solvent	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Benzoic acid	= 1700 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	> 26 mg/m ³ (Rat) 1 h > 12.2 mg/L (Rat) 4 h
Calcium petroleum sulfonate	> 20 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Naphthenic acids, zinc salts	= 4920 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 11.6 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated middle	= 7400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 4.6 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available

Mutagenic Effects This product contains a substance which has been classified in the EU as mutagenic

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity No information available

STOT - single exposure No information available

STOT - repeated exposure No information available

Aspiration Hazard No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 6993 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Stearic acid 57-11-4		LC50 96 h: < 3000 mg/L semi-static (Brachydanio rerio)		
Silica 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
Naphtha (petroleum), hydrotreated heavy 64742-48-9		LC50 96 h: = 2200 mg/L (Pimephales promelas)		LC50 96 h: = 2.6 mg/L (Chaetogammarus marinus)

Aromatic solvent 64742-95-6		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Benzoic acid 65-85-0	EC50 3 h: = 5 mg/L (Anabaena inaequalis)	LC50 96 h: = 180 mg/L (Gambusia affinis)		EC50 24 h: = 300 mg/L (Daphnia magna) EC50 48 h: = 860 mg/L Static (Daphnia magna)
Copper 7440-50-8	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)	-	EC50 48 h: = 0.03 mg/L Static (Daphnia magna)
Calcium petroleum sulfonate 61789-86-4		LC50 96 h: 1.0 - 10.0 mg/L semi-static (Pimephales promelas) LC50 96 h: 5.7 - 9.7 mg/L static (Pimephales promelas)		EC50 48 h: 6.2 - 12 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated middle 64742-46-7		LC50: 35 mg/L Pimephales promelas 96 h flow-through LC50: >10000 mg/L Pimephales promelas 96 h static		

Persistence and Degradability No information available

Bioaccumulation No information available

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Contact supplier for inventory compliance status
DSL/NDSL Contact supplier for inventory compliance status

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Aluminum	7429-90-5	5	1.0
Copper (metallic)	7440-50-8	1	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Petroleum distillates, hydrotreated heavy naphthenic				X	
Silica		X	X		
Aluminum	X	X	X		X
Copper (metallic)	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1	Flammability 0	Physical Hazard 0	Personal Protection X

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	13-Nov-2014
Revision Date	15-Nov-2018
Revision Note	Added VOC content.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet